Ultrasolve Cleaning Solvent

Product Code: ULS

PRODUCT DESCRIPTION

Ultrasolve Cleaning Solvent is a fast-drying solvent specially formulated for the quick and efficient cleaning of electrical equipment. It replaces CFC solvents such as 113 trichloroethane due to rapid cleaning and fast evaporation rates. Ultrasolve is 100% Ozone Friendly. A full range of cleaning solvents are available from Electrolube. The range includes fast and slow drying solvents and water based products. Specialist flux cleaners are also available.

PRODUCT USE

Electrical contacts, tape heads, PCBs, components in electronic and video equipment, computers, optical and precision instruments, cameras etc. Product contains **flammable solvent** so do not spray onto live electrical equipment or other sources of ignition. Immerse surface to be cleaned or spray onto surface to excess and allow to evaporate. A brush or foam tipped bud may be used to remove any stubborn deposits.

FEATURES

- * Non-CFC, non-halogenated cleaning solvent will not attack the Ozone Layer.
- * Excellent removal of greases, oils, flux residues and acrylic conformal coatings from PCBs.
- * Leaves a perfectly clean, dry surface conventional solvents often leave greasy deposits which attract dust and dirt.
- * Harmless to most plastics, rubbers, elastomers, and surface coatings.
- * CO₂ propelled aerosol version available containing 20% more active cleaner.

PROPERTIES

Specific Gravity @ 20°C: Inhalation Toxicity: Flash Point: 0.79 300 ppm -20°C



ELECTROLUBE, A division of H K Wentworth, Kingsbury Park, Midland Road, Swadlincote, Derbyshire, DE11 0AN Tel: +44(0) 1283-222111 Fax: +44(0) 1283-550177 www.electrolube.com ISO 9002 Registered Firm. Certificate No. FM 32082

TECHNICAL DATA SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

<u>Ultrasolve Cleaning Solvent</u> – Page 2

Residue on Evaporation: Evaporation Rate:

PACKAGING

12ml Pen - Packed in 5's 200ml Aerosol 400ml Aerosol 400ml Aerosol with Brush 1 Litre Bulk 5 Litre Bulk 25 Litre Bulk <1ppm 16 (with ether as 1)

ORDER CODE

ULS12P ULS200D ULS400D ULS400DB ULS01L ULS05L ULS25L TECHNICAL DATA SHEET



Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer. who must satisfy themselves as to the suitability of the product.



ELECTROLUBE, A division of H K Wentworth, Kingsbury Park, Midland Road, Swadlincote, Derbyshire, DE11 0AN Tel: +44(0) 1283-222111 Fax: +44(0) 1283-550177 www.electrolube.com ISO 9002 Registered Firm. Certificate No. FM 32082